

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATIENT COOPERATION TREATY (PCT)

31 (mernational Patent Classification 6 W() 99/36755 (11) International Publication Number A1 G01K 3/04 (43) International Publication Date: 22 July 1999 (22:07 99) 21) International Application Stumber:

PCT/GB99/00044

22) International Filing Date:

(8 January 1999 (18 01.99)

30 Priority Datus

9800514.7

16 January 1998 (16 01.98)

CB

"In Applicant for all assignated States except (15): FOOD GU ARDIAN LIMITED (GB/GB); Ashrields, Leigh Sinton, Maltem Worcestershire WR15 5DH (GB).

2) Inventors; and

.751 Inventors/Applicants (for US only): MOULE, Robert [GB GB]. Chygumo Lamorna. Penzance TR19 6XH (GB). MOULE, Simon [GB/GB], 42 Encymion Road, London N4 TEQ (GB).

(\*4) Agent. ATKINSON, Peter, Birch: Marks & Clerk, Sussex House, \$3-85 Mosley Street, Manchester M2 3LG (GB),

(NI) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP. KR. KZ. LC. I.K. LR, LS, LT. LU, LV. MD, MG. NK. MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG. SI SK. SL, II. TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW. ARIPO patent (GH. OM. KE, LS, MW. SD. SZ, UG. ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CJ, CM, GA, GN, GW, ML, MR, NE, 3N, TD, TG)


Published

With international search report

(54) Title: BARRIER MATERIALS AND PRODUCTS PRODUCED THEREWITH

(57) Abstract

A marking element cla for indicating whether 2 pre-Jefined temperature condition has been maintained. The element comprises a first material (7) s svode animon to sleeper predetermined temperature



separated from a second absorbent material (5, 10) by a heat disruptable barrier layer (4). The first and second materials are such that when the barrier layer is punctured and the oredetermined temperature is exceeded the first material flows in the second material to produce 2 detectable change. The heat disruptable barrier layer (4) is comprised of a heat disruptable material (8) associated with an element (9) capable of being inductively heated by electromagnetic energy to effect disruption of said material thereby to activate the marking element.

T. The little M , D Han Han ĚÁ